

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E510840  
**Report Reference** E510840-20210129  
**Date** 2021-April-01

**Issued to:** DONG A BESTECH CO LTD  
54 Songnae-daero 518beon-gil  
Ojeong-gu  
Bucheon-siGyeonggi-do 421-808 KR

**This is to certify that  
representative samples of**

CABLE FITTINGS FOR USE IN ZONE CLASSIFIED  
HAZARDOUS LOCATIONS

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** See Addendum Page for Standards

**Additional Information:** See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E510840  
**Report Reference** E510840-20210129  
**Date** 2021-April-01

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Cable Fittings for use in Hazardous Locations, Class I, Zone 1, AEx eb IIC Gb, Zone 21, AEx tb IIIC Db.

A2F, A2FRC, SS2k cable gland fittings for use with TC, TC-ER, and TC-ER-HL tray cable. Sizes M20, M25, M32, M40, M50, M63, M75, M80, M90, M100, 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 3-1/2", 4".

DNEX, DEX, DNLEX, DLEX cable gland fittings for use with TC, TC-ER, and TC-ER-HL tray cable. Sizes M16, M20, M25, M32, M40, M50, M63, M75, M80, M90, M100, 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 3-1/2", 4".

Cable Fittings for use in Hazardous Locations, Class I, Zone 1, Ex db IIC Gb, Ex eb IIC Gb, Zone 21, Ex tb IIIC Db.

A2F, A2FRC, SS2k cable gland fittings for use with TC, TC-ER, and TC-ER-HL tray cable. Sizes M20, M25, M32, M40, M50, M63, M75, M80, M90, M100, 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 3-1/2", 4".

DNEX, DEX, DNLEX, DLEX cable gland fittings for use with TC, TC-ER, and TC-ER-HL tray cable. Sizes M16, M20, M25, M32, M40, M50, M63, M75, M80, M90, M100, 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 3-1/2", 4".

## Standards for Safety:

UL 2225, Cables and Cable-Fittings for Use in Hazardous (Classified) Locations

CSA C22.2 No. 60079-0:19, Explosive atmospheres – Part 0: Equipment – General requirements

CAN/CSA-C22.2 No. 60079-1:16, Explosive atmospheres — Part 1: Equipment protection by flameproof enclosures "d"

CAN/CSA-C22.2 No. 60079-7:16, Explosive atmospheres — Part 7: Equipment protection by increased safety "e"

CAN/CSA-C22.2 No. 60079-31:15, Explosive atmospheres — Part 31: Equipment dust ignition protection by enclosure "t"

UL 514B, Conduit, Tubing, and Cable Fittings

CAN/CSA-C22.2 No. 18.3-12, Conduit, Tubing, and Cable Fittings



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>